

# **BEACON LINE**

## **Technical Reference**

## Beacon Line Node



Sample picture: The product supplied will differ from the picture (picture © Bopla)

<b>Technical data</b>	
Size	90 mm x 33 mm
Weight	24 g (w/o housing)
Operating temperature	-40 to 85 °C
Protection class	IP65
Connection method	RJ45
Power supply	Passive PoE <sup>1</sup> (12-24V)
Bluetooth class	Bluetooth low energy 4.0
Max nodes	15
BLE Role	Observer and Broadcaster
BLE Filtering	ibeacon packet
BLE-module	U.FL connector
BLE antenna	U.FL-Adhesive Antenna (2.4 GHz ~ 2.48GHz)
Housing	200 x 150 (ABS)
Fixation	4 x Power Magnets á 25 kg

## **Glossary**

1. Passive PoETM (Power over Ethernet) is a simple way of providing power to an access point through an ethernet cable. Passive PoETM uses free wires in the ethernet cable to send the equipment's power along them to the other end.

## **BEACON LINE**

Web: [www.beacon-line.com](http://www.beacon-line.com)

Tel: +49(0)30 / 611295-46

Fax: +49(0)30 / 611295-10

taskit GmbH Groß-Berliner Damm 37, 12487 Berlin, Deutschland

Amtsgericht Berlin-Charlottenburg HRB 39014

Geschäftsführer Dipl.-Ing. (FH) Thorsten Raulfs